

EA900G4

6 kVA ~ 20 kVA (1:1)

PF 1.0



Features

- Advanced DSP (Digital signal processors) technology
- Variable speed fan
- Effective software and hardware protection function, robust self-diagnostic function, and abundant event log for check
- Advanced digital parallel technology
- Wide input voltage range, 50 / 60 Hz frequency auto sensing
- Linear derating in low voltage input reducing battery discharging times, extending the service life of battery
- Dual-input design, supporting independent bypass
- Output power factor improved from 0.9 to 1, load capacity increased by 13%
- Flexible battery configuration (settable 16 - 20 pcs batteries)
- Charging voltage and current configured by demands
- Ability to switch on the UPS with batteries
- Settable delayed start time when mains power is restored, reducing the impact on power grid or generator
- Two modes of frequency conversion: 50 Hz input / 60 Hz output or 60 Hz input / 50 Hz output

- LCD+LED display, multi-functional keys operation, friendly human-machine interface
- Powerful background software for parameters configuration
- Compact internal layout, miniaturized the complete unit for small footprint
- Advanced multi-platform communications: RS232, USB, RS485, SNMP and dry contacts communication interfaces
- Intelligent battery management, automatic floating / equalizing charge control, charger dormancy control, increasing battery life by 50%
- Active power factor correction (APFC), input power factor up to 0.99
- High efficiency 95% (up to 98% in ECO mode)
- Equipped with self-aging function

Available Options

- RS232 and smart card slot included
- Optional parallel function, battery temperature compensation, SNMP card, USB, RS485 card, dry contacts, EMD, and SMS alarms

Rear Panel

1. RS232
2. EPO
3. Parallel port (optional)
4. USB (optional)
5. Temperature detection (optional)
6. SNMP (optional)
7. Reserved: for customer function such as manual bypass, battery breaker, socket ect.
8. Fans
9. Bypass breaker
10. Input breaker
11. GND
12. Terminals and terminal cover



6 kH / 10 kH

15 kH / 20 kH

6 kS / 10 kS

Specifications

MODEL	6 kVA	10 kVA	15 kVA	20 kVA
Capacity	6 kVA / 6000 W	10 kVA / 10000 W	15 kVA / 15000 W	20 kVA / 20000 W
INPUT				
Input wiring	Single-phase three-wire (1Φ + N + PE)			
Rated voltage	208 V / 220 V / 230 V / 240 Vac			
Voltage range	110 ~ 176 Vac (linear derating between 50% and 100% load); 176 ~ 288 Vac (no derating)			
Rated frequency	50 / 60 Hz (auto-sensing)			
Frequency range	40 ~ 70 Hz			
Power factor	≥ 0.99			
Bypass voltage range	- 40% ~ +15% (settable)			
Total harmonic distortion (THDI)	≤ 5%			
OUTPUT				
Output wiring	Single-phase three-wire (1Φ + N + PE)			
Rated voltage	208 V (PF=0.9) / 220 V / 230 V / 240 Vac			
Voltage regulation	± 1%			
Frequency	Synchronized to bypass in mains mode; 50 / 60 Hz ± 0.1% Hz in battery mode			
Waveform	Sinusoidal			
Power factor	1			
Total harmonic distortion (THDV)	≤ 1% (linear load); ≤ 4% (non-linear load)		≤ 1% (linear load); ≤ 3% (non-linear load)	
Crest factor	3:1			
Overload capability	102% ~ 110% for 10 min, 110% ~ 125% for 1 min, 125% ~ 150% for 30 s			
BATTERIES				
DC voltage	192 Vdc (192 / 240 Vdc settable)			
Number of battery	16 pcs (16 ~ 20 settable)			
Inbuilt battery (standard model)	12 / 7 Ah × 16	12 / 9 Ah × 16	/	/
Charging current	Standard model: 1 A; Long time model: 5 A (default), 1 ~ 5 A settable; 12 A (6-10 kVA optional); 10 A (15-20 kVA optional)			
Recharge time	Standard model: 90% capacity restored in 8 hours; Long time model: depend on the capacity of battery			
SYSTEM				
Efficiency	≥ 94% at 100% load, max. 95% at 60% load; ≥ 98% in ECO mode			
Switching time	0 ms			
Protections	Short-circuit, overload, overtemperature, battery low voltage, overvoltage, undervoltage and fan failure			
Max. number of parallel connections	4			
Communications	RS232 (standard), USB / RS485 / dry contacts / SNMP / battery temperature compensation (optional)			
Display	LCD + LED			
OTHERS				
Operating temperature	0°C ~ 45°C			
Storage temperature	-25°C ~ 55°C (without battery)			
Humidity	0 ~ 95% (non-condensing)			
Altitude	≤ 1000 m, derating 1% for each additional 100 m			
IP rating	IP 20			
Noise level at 1 m	≤ 55 dB		≤ 58 dB	
Dimensions (W × D × H) (mm)	191 × 465 × 711 (S) 191 × 465 × 350 (H)	191 × 495 × 711 (S) 191 × 495 × 350 (H)	191 × 495 × 515 (H)	
Packaged dimensions (W × D × H) (mm)	654 × 310 × 941 (S) 595 × 318 × 475 (H)	685 × 310 × 941 (S) 617 × 318 × 475 (H)	593 × 285 × 618 (H)	
Net weight (kg)	53 (S) 14.5 (H)	62 (S) 16.5 (H)	26.5 (H)	
Gross weight (kg)	61 (S) 16 (H)	70 (S) 18 (H)	28 (H)	

• S means standard model; H means long time model.
• All specifications are subject to change without notice.

A Product of

Voltronic Technologies Pvt. Ltd.

No.14/1, 5th Cross Extn, Bharathi Nagar, Ganapathy Post, Coimbatore - 641 006.
Phone: +91 99424 35183, 0422 2511655, Email: info@voltronictechnologies.com
Website: www.voltronictechnologies.com

Associate Business Partner



voltronic

THE SIGN OF TECHNOLOGY

EA900G4

6 kVA ~ 20 kVA (3:1)

PF 1.0



Features

- Advanced DSP (Digital signal processors) technology
- Variable speed fan
- Effective software and hardware protection function, robust self-diagnostic function, and abundant event log for check
- Advanced digital parallel technology
- Wide input voltage range, 50 / 60 Hz frequency auto sensing
- Linear derating in low voltage input reducing battery discharging times, extending the service life of battery
- Dual-input design, supporting independent bypass
- Output power factor improved from 0.9 to 1, load capacity increased by 13%
- Flexible battery configuration (settable 16 - 20 pcs batteries)
- Charging voltage and current configured by demands
- Ability to switch on the UPS with batteries
- Settable delayed start time when mains power is restored, reducing the impact on power grid or generator
- Two modes of frequency conversion: 50 Hz input / 60 Hz output or 60 Hz input / 50 Hz output

- LCD+LED display, multi-functional keys operation, friendly human-machine interface
- Powerful background software for parameters configuration
- Compact internal layout, miniaturized the complete unit for small footprint
- Advanced multi-platform communications: RS232, USB, RS485, SNMP and dry contacts communication interfaces
- Intelligent battery management, automatic floating / equalizing charge control, charger dormancy control, increasing battery life by 50%
- Active power factor correction (APFC), input power factor up to 0.99
- High efficiency 95% (up to 98% in ECO mode)
- Equipped with self-aging function

Available Options

- RS232 and smart card slot included
- Optional parallel function, battery temperature compensation, SNMP card, USB, RS485 card, dry contacts, EMD, and SMS alarms

Rear Panel

1. RS232
2. EPO
3. Parallel port (optional)
4. USB (optional)
5. Temperature detection (optional)
6. SNMP (optional)
7. Reserved: for customer function such as manual bypass, battery breaker, socket ect.
8. Fans
9. Bypass breaker
10. Input breaker
11. GND
12. Terminals and terminal cover



6 kH / 10 kH

15 kH / 20 kH

6 kS / 10 kS

Specifications

MODEL	6 kVA	10 kVA	15 kVA	20 kVA
Capacity	6 kVA / 6000 W	10 kVA / 10000 W	15 kVA / 15000 W	20 kVA / 20000 W
INPUT				
Input wiring	Three-phase five-wire (3 Φ + N + PE)			
Rated voltage	380 V / 400 V / 415 Vac			
Voltage range	190 ~ 305 Vac (linear derating between 50% and 100% load); 305 ~ 499 Vac (no derating)			
Rated frequency	50 / 60 Hz (auto-sensing)			
Frequency range	40 ~ 70 Hz			
Power factor	\geq 0.99			
Bypass voltage range	- 40% ~ +15% (settable)			
Total harmonic distortion (THDI)	\leq 5%			
OUTPUT				
Output wiring	Single-phase three-wire (1 Φ + N + PE)			
Rated voltage	208 V (PF=0.9) / 220 V / 230 V / 240 Vac			
Voltage regulation	\pm 1%			
Frequency	Synchronized to bypass in mains mode; 50 / 60 Hz \pm 0.1% Hz in battery mode			
Waveform	Sinusoidal			
Power factor	1			
Total harmonic distortion (THDV)	\leq 1% (linear load); \leq 3% (non-linear load)			
Crest factor	3:1			
Overload capability	102% ~ 110% for 10 min, 110% ~ 125% for 1 min, 125% ~ 150% for 30 s			
BATTERIES				
DC voltage	192 Vdc (192 / 240 Vdc settable)			
Number of battery	16 pcs (16 ~ 20 settable)			
Inbuilt battery (standard model)	12 / 7 Ah \times 16	12 / 9 Ah \times 16	/	/
Charging current	Standard model: 1 A; Long time model: 5 A (default), 1 ~ 5 A settable; 10 A (optional)			
Recharge time	Standard model: 90% capacity restored in 8 hours; Long time model: depend on the capacity of battery			
SYSTEM				
Efficiency	\geq 94% at 100% load, max. 95% at 60% load, \geq 98% in ECO mode			
Switching time	0 ms			
Protections	Short-circuit, overload, overtemperature, battery low voltage, overvoltage, undervoltage and fan failure			
Max. number of parallel connections	4			
Communications	RS232 (standard), USB / RS485 / dry contacts / SNMP / battery temperature compensation (optional)			
Display	LCD + LED			
OTHERS				
Operating temperature	0 $^{\circ}$ C ~ 45 $^{\circ}$ C			
Storage temperature	-25 $^{\circ}$ C ~ 55 $^{\circ}$ C (without battery)			
Humidity	0 ~ 95% (non-condensing)			
Altitude	\leq 1000 m, derating 1% for each additional 100 m			
IP rating	IP 20			
Noise level at 1 m	\leq 58 dB			
Dimensions (W \times D \times H) (mm)	191 \times 495 \times 711 (S) 191 \times 495 \times 350 (H)		191 \times 495 \times 515 (H)	
Packaged dimensions (W \times D \times H) (mm)	685 \times 310 \times 941 (S) 617 \times 318 \times 475 (H)		593 \times 285 \times 618 (H)	
Net weight (kg)	58.5 (S) 18.5 (H)	64 (S) 18.5 (H)	26.5 (H)	
Gross weight (kg)	66.5 (S) 20 (H)	72 (S) 20 (H)	28 (H)	

• S means standard model; H means long time model.
• All specifications are subject to change without notice.

A Product of

Voltronic Technologies Pvt. Ltd.

No.14/1, 5th Cross Extn, Bharathi Nagar, Ganapathy Post, Coimbatore - 641 006.
Phone: +91 99424 35183, 0422 2511655, Email: info@voltronictechnologies.com
Website: www.voltronictechnologies.com

Associate Business Partner